

Notstromaggregate » Stromerzeuger » 24 Std. Service

Stationary power gen set as emergency power system 30 kVA with Deutz engine

Technical Data Engine: Engine Manufacturer: Deutz Engine Type: F 4 M 2011 Engine No.: diverse Engine Power: 27 KW Cooling: oil-cooled Starting: electrical 12 V DC Rotation: 1500 rpm Fuel: heating oil EN 590 Technical Data Generator:	Generating Set:	stationary	Gen Set:	silent Set
Engine No.:diverseEngine Power:27 KWCooling:oil-cooledStarting:electrical 12 V DCRotation:1500 pmFuel:heating oil EN 590Technical Data Generator:Egnerator Manufacturer:SynchronGenerator Manufacturer:Stamford AvKGen Set:SynchronGenerator Manufacturer:Stamford AvKGen Set:SynchronGenerator Manufacturer:Stamford AvKGen Set:SynchronGenerator Manufacturer:Stamford AvKGen Power:30 kVAVoltage:400 / 231 VoltPower Factor:cos phi 0,8Rotation:1500 pmControl Unit:cos phi 0,8Control Unit:Setup:automatic startFunctions:RemotestartSwitch:gen switch 4 poleDelivery:set upWidth ca. mm:Width ca. mm:gen switch 4 poleDepth ca. mm:Setup:Setup:Set upSet upSet up-Width ca. mm:GoHeight ca. mm:SoSoDepth ca. mm:2.000Weight ca. KG:1.236-Width ca. mm:960Weight ca. KG:1.075-Usage:SoldPrice plus VAT in iz ½:on request:-State:demonstration setyear of manufacture:2022-Usage:soldPrice plus VAT in iz ½:on request:-Location:Veri - GermanySoState:SoldSoldSet up </td <td>Technical Data Engine:</td> <td></td> <td></td> <td></td>	Technical Data Engine:			
Cooling:oil-cooledSarting:electrical 12 V DCRotation:1500 rpmFuel:heating oil EN 590Technical Data Generator:Generator Manufacturer:Stamford AvKGen Set:SynchronGen No.:DiverseGen Set:SynchronKottage:400 / 231 VoltPower Factor:cos phi 0,8Rotation:1500 rpmControl Unit:cos phi 0,8Control Unit:sutomatic startFunctions:RemotestartSwitch:gen switch 4 poleDelivery:set upWidth ca. mm:gen switch 4 poleDepth ca. mm:cos phi 0,8TankSetup:Setup:set upSetup:Sutomatic startHeight ca. mm:cos phi 0,8Depth ca. mm:2.000Noteset upDividth ca. mm:960Setup:cos phi 0,8Vidth ca. mm:2.000Height ca. mm:1.236Width ca. mm:960Weigth ca. KG:1.075Usage:State:demonstration setyear of manufacture:2022Usage:soldPrice plus VAT in i¿½:on request:Operating Hours:2coston:Yeir Germanycoston:	Engine Manufacturer:	Deutz	Engine Type:	F 4 M 2011
Rotation:1500 rpmFuel:heating oil EN 590Technical Data Generator:	Engine No.:	diverse	Engine Power:	27 KW
Technical Data Generator:Stamford AvKGen Set:SynchronGenerator Manufacturer:DiverseGen Power:30 kVAVoltage:400 / 231 VoltPower Factor:cos phi 0,8Kotation:1500 rpmControl Unit:cos phi 0,8Control Unit:automatic startFunctions:RemotestartSwitch:gen switch 4 poleDelivery:set upWidth ca. mm:gen switch 4 poleDelivery:set upWidth ca. mm:Image: Set upDepth ca. mm:Image: Set upSetup:Image: Setup:Setup:Setup:Width ca. mm:Image: Setup:Setup:Setup:Width ca. mm:Image: Setup:Setup:Setup:Width ca. mm:Image: Setup:Setup:Setup:Width ca. mm:960Weigth ca. mm:1.236Unit:Setup:Image: Setup:Image: Setup:Setup:Setup:Setup:Image: Setup:Width ca. mm:Setup:Setup:Setup:Width ca. mm:Setup:	Cooling:	oil-cooled	Starting:	electrical 12 V DC
Generator Manufacturer:Stamford AvKGen Set:SynchronGen No.:DiverseGen Power:30 kVAVoltage:400 / 231 VoltPower Factor:cos phi 0,8Rotation:1500 rpmCost-Control Unit:set uomatic startFunctions:RemotestartSetup:automatic startFunctions:RemotestartSwitch:gen switch 4 poleDelivery:set upWidth ca. mm:gen switch 4 poleDepth ca. mm:-TankTankTankStup:-Capacity / Litre:50Dimensions of unit:-Capacity / Litre:50Dimensions of unit:Length ca. mm:960Weigth ca. KG:1.075Usage:State:demonstration setyear of manufacture:2022Price plus VAT in �:on request:-Operating Hours:2Location:Verl - Germany	Rotation:	1500 rpm	Fuel:	heating oil EN 590
Gen No.:DiverseGen Power:30 kVAVoltage:400 / 231 VoltPower Factor:cos phi 0,8Rotation:1500 rpmPower Factor:cos phi 0,8Control Unit:sutomatic startFunctions:RemotestartSwitch:gen switch 4 poleDelivery:set upWidth ca. mm:pepth ca. mm:Depth ca. mm:FankSetup:Setup:Setup:Width ca. mm:Capacity / Litre:50Depth ca. mm:2.000Height ca. mm:1.236Dimensions of unit:Setup:1.236Usage:Setup:1.075Usage:Setup:Setup:Usage:Setup:Setup:Usage:Setup:Setup:Usage:Setup:Setup:Usage:Setup:Setup:Usage:Setup:Setup:Usage:Setup:Setup:Usage:Setup:Setup:Usage:Setup:Setup:Usage:Setup:Setup:Usage:Setup:Setup:State:demonstration setyear of manufacture:SoldPrice plus VAT in �:on request:Operating Hours:2Setup:Location:Verl - Germany	Technical Data Generator:			
Voltage: Rotation:400 / 231 Volt 1500 rpmPower Factor: cos phi 0,8Control Unit:1500 rpmCos phi 0,8Control Unit:Entropy of the poleFunctions: Delivery: Depth ca. mm:RemotestartWidth ca. mm: Height ca. mm:gen switch 4 poleDelivery: Depth ca. mm:set upSetup: Setup:Image: Set upSet upSet upWidth ca. mm: Depth ca. mm:Image: Set upImage: Set upWidth ca. mm: Depth ca. mm:Image: Set upImage: Set upWidth ca. mm: Depth ca. mm:Image: Set upImage: Set upDimensions of unit: Length ca. mm: Depth ca. mm:1.236Image: Set upDimensions of unit: Length ca. mm: Dego: Set upImage: Set upImage: Set upState: Image: Set updemonstration set Soldyear of manufacture: Price plus VAT in �: Set up2022Dimension: Usage: Location:2Verl - GermanyImage: Set up	Generator Manufacturer:	Stamford AvK	Gen Set:	Synchron
Rotation:1500 rpmInterfaceControl Unit:automatic startFunctions:RemotestartSetup:automatic startPuelivery:set upWidth ca. mm:gen switch 4 poleDelivery:set upDepth ca. mm:Depth ca. mm:Depth ca. mm:Height ca. mm:Setup:Width ca. mm:Setup:Width ca. mm:Depth ca. mm:Usage:Usage:Usage:Usage:Usage:Usage:Usage:Usage:Usage:Usage:Usage:<	Gen No.:	Diverse	Gen Power:	30 kVA
Control Unit: Setup: automatic start Functions: Remotestart Switch: gen switch 4 pole Delivery: set up Width ca. mm: Depth ca. mm: Depth ca. mm: Height ca. mm: Image: Control Unit: Image: Control Unit: Tank Setup: Image: Control Unit: Image: Control Unit: Dimensions of unit: Image: Control Unit: Image: Control Unit: Image: Control Unit: Usage: State: demonstration set year of manufacture: 2022 Usage: Sold Price plus VAT in �: on request: Operating Hours: 2 Verl - Germany Image: Control Unit:	Voltage:	400 / 231 Volt	Power Factor:	cos phi 0,8
Setup:automatic startFunctions:RemotestartSwitch:gen switch 4 poleDelivery:set upWidth ca. mm:Depth ca. mm:Depth ca. mm:Height ca. mm:TankSetup:Width ca. mm:Depth ca. mm:Setup:Width ca. mm:Depth ca. mm:Depth ca. mm:-50Dimensions of unit:Length ca. mm:2.000Height ca. Mm:1.236Width ca. mm:060Weigth ca. KG:1.075Usage:State:demonstration setyear of manufacture:2022Itime of delivery:soldPrice plus VAT in ï¿%:on request:Operating Hours:2Location:Verl - Germany	Rotation:	1500 rpm		
Switch:gen switch 4 poleDelivery:set upWidth ca. mm:Depth ca. mm:Depth ca. mm:Height ca. mm:Image: Capacity / Litre:Image: Capacity / Litre:Setup:Solution:Solution:Width ca. mm:Image: Capacity / Litre:Image: Capacity / Litre:Dimensions of unit:Image: Capacity / Litre:Image: Capacity / Litre:Usage:Image: Capacity / Litre:Image: Capacity / Litre:State:Genostration setImage: Capacity / Litre:State:SoldPrice plus VAT in �:On request:Operating Hours:2Image: Capacity / Litre:Image: Capacity / Litre:State:SoldPrice plus VAT in �:Image: Capacity / Litre:Capacity Hours:2Image: Capacity / Litre:Image: Capacity / Litre:State:SoldSoldPrice plus VAT in �:Image: Capacity / Litre:Capacity Hours:SoldSoldSoldImage: Capacity / Litre:State:SoldSoldSoldImage: Capacity / Litre:State:SoldSoldS	Control Unit:			
Width ca. mm: Depth ca. mm: Height ca. mm: Image: Capacity / Litre: Setup: Height ca. mm: Width ca. mm: Capacity / Litre: Depth ca. mm: 50 Dimensions of unit: Image: Capacity / Litre: Length ca. mm: 960 Width ca. mm: 1.236 Width ca. mm: 0.000 Beight ca. mm: 1.236 Usage: 1.075 Usage: Usage: Utime of delivery: sold Operating Hours: 2 Location: Verl - Germany	Setup:	automatic start	Functions:	Remotestart
Height ca. mm: Image: Capacity / Litre: Image: Capacity / Litre:<	Switch:	gen switch 4 pole	Delivery:	set up
Tank Setup: Width ca. mm: Height ca. mm: Depth ca. mm: Capacity / Litre: Dimensions of unit: Length ca. mm: 2.000 Height ca. mm: 1.236 Width ca. mm: 960 Weigh ca. KG: 1.075 Usage: State: time of delivery: sold Operating Hours: 2 Location: Verl - Germany	Width ca. mm:		Depth ca. mm:	
Setup: Height ca. mm: Image: Capacity / Litre: 50 Depth ca. mm: 2.000 Height ca. mm: 1.236 Dimensions of unit: Image: Capacity / Litre: 1.236 Width ca. mm: 960 Weight ca. KG: 1.075 Usage: Image: Capacity / Litre: 2022 State: demonstration set year of manufacture: 2022 Operating Hours: 2 2 Image: Capacity / Litre: 1mage: Capacity / Litre: Usage: Usage: Usage: Capacity / Litre: Capacity / Litre: Capacity / Litre: Usage: Usage: Usage: Capacity / Litre: Capacity / Litre: Capacity / Litre: Usage: Usage: Usage: Capacity / Litre: Capacity / Litre: Capacity / Litre: Usage: Usage: Usage: Capacity / Litre: Capacity / Litre: Capacity / Litre: Usage: Sold Price plus VAT in �: On request: Usage: Usage: Usage: Capacity / Litre: Capacity / Litre: Usage: Capacity / Litre: Capacity / Litre: Capacity / Litre: Usage: Sold Price plus VAT in	Height ca. mm:			
Widh ca. mm: Height ca. mm: Height ca. mm: Depth ca. mm: 50 Dimensions of unit: 50 Length ca. mm: 2.000 Midth ca. mm: 960 Weight ca. mm: 1.236 Wight ca. mm: 960 Weight ca. KG: 1.075 Usage: 50 Utime of delivery: sold Sold Price plus VAT in is ½: Operating Hours: 2 Location: Verl - Germany	Tank			
Depth ca. mm: Capacity / Litre: 50 Dimensions of unit: Length ca. mm: 1.236 Width ca. mm: 960 Weigth ca. KG: 1.075 Usage: State: demonstration set year of manufacture: 2022 time of delivery: sold Price plus VAT in �: on request: Operating Hours: 2 Verl - Germany Verl - Germany	Setup:			
Dimensions of unit: Length ca. mm: 1.236 Length ca. mm: 960 Weight ca. KG: 1.075 Usage: State: demonstration set year of manufacture: 2022 time of delivery: sold Price plus VAT in �: on request: Operating Hours: 2 Verl - Germany Location:	Width ca. mm:		Height ca. mm:	
Length ca. mm: 2.000 Height ca. mm: 1.236 Width ca. mm: 960 Weigh ca. KG: 1.075 Usage: 1.075 Usage: 2022 State: demonstration set year of manufacture: 2022 time of delivery: sold Price plus VAT in �: on request: Operating Hours: 2 Verl - Germany	Depth ca. mm:		Capacity / Litre:	50
Width ca. mm: 960 Weigth ca. KG: 1.075 Usage: State: demonstration set year of manufacture: 2022 time of delivery: sold Price plus VAT in �: on request: Operating Hours: 2 Contine Verl - Germany	Dimensions of unit:			
Usage: demonstration set year of manufacture: 2022 State: demonstration set Price plus VAT in ĩ¿½: on request: Operating Hours: 2 Verl - Germany	Length ca. mm:	2.000	Height ca. mm:	1.236
State: demonstration set year of manufacture: 2022 time of delivery: sold Price plus VAT in �: on request: Operating Hours: 2 Verl - Germany	Width ca. mm:	960	Weigth ca. KG:	1.075
time of delivery: sold Price plus VAT in �: on request: Operating Hours: 2 0 0 Location: Verl - Germany Verl - Germany 0	Usage:			
Operating Hours: 2 Location: Verl - Germany	State:	demonstration set	year of manufacture:	2022
Location: Verl - Germany	time of delivery:	sold	Price plus VAT in �:	on request:
	Operating Hours:	2		
	Location:	Verl - Germany		
Stock No: Reserved: nein / no	Stock No:		Reserved:	nein / no

Delivery Contents:

Emergency generator as a mains backup system for the emergency power supply as a backup power system with an original Deutz industrial diesel engine with speed control and a Stamford three-phase synchronous generator. Motor and generator are mounted elastically on a common skid frame. Installed in a modular soundproofing enclosure.

Powder-coated in RAL 3000

Other additional features:

Tank capacity 50 liters, refueling directly at the tank

2.14 liters / hour at 25% load 4.07 liters / hour at 50% load 5.46 liters / hour at 75% load 7.18 liters / hour at 100% load

Internal automatic start-stop (type: AMF DSE 4150) with display of all engine and generator messages. Functional indication digitally on the display. Generator switch 40 amps 4 poles integrated in the unit (generator). Internal battery charger 230 volts - 12 volts DC

Optionally available at extra cost:

Automatic start with mains & generator switching 4-pole

External emergency power switchgear for installation in the building and 4-pole mains generator switchover

Function: In the event of a power failure, the start command is transferred to the diesel generator set. When the rated speed and rated voltage is replaced, the generator switch WILL be switched on. When the mains returns, the automatic system monitors the mains voltage. When this is stable again, the system switches back to mains operation. The diesel genset WILL be stopped after the cooling time and waits in automatic mode for the next power failure.

The emergency power system as an emergency power supply is ready for operation and immediately available from stock.

Product Images























Notstromaggregate » Stromerzeuger » 24 Std. Service









